



3512E Non-Road China Stage III Engine

2237 bkW
(3000 bhp)
1900 rpm

Dry Manifold with ATAAC




Image is a representation only, and may show optional attachments.

CAT® ENGINE SPECIFICATIONS

V-12, 4-Stroke-Cycle-Diesel

Emissions	China Non Road Mobile Stage III Emissions Certified
Peak Torque at Speed.....	8292.6 lbs-ft
Bore.....	170 mm (6.7 in)
Stroke	215 mm (8.5 in)
Displacement	58.6 L (3574 in ³)
Aspiration	Turbocharged-Aftercooled Governor and Protection
Engine Weight, net dry (approx)	Electronic (ADEM™ A5) 6400 kg (14,110 lb)
Capacity for Liquids	
Lube Oil System (refill)	151.4 L (40 gal)
Cooling System	156.7 L (41.4 gal)
Oil Change Interval*	250 hours
Rotation (from flywheel end)	Counterclockwise
Flywheel and Flywheel Housing	SAE No. 0
Flywheel Teeth.....	151
*500 hours oil sump pan optional	

FEATURES

Engine Design

- Proven reliability and durability
- Robust diesel strength design prolongs life and lowers owning and operating costs
- Broad operating speed range

Cooling System

Air-to-Air Aftercooled (ATAAC)

Optional Attachments

Engine Mounted Transmission Oil Cooler —

Integration with engine cooling system allows ease of installation and a tighter overall engine package

Advanced Digital Engine Management

ADEM A5 engine management system integrates speed control, and ignition/detonation controls into a complete engine management system with integrated digital ignition, engine protection and monitoring

Custom Packaging

For any petroleum application, trust Caterpillar to meet your exact needs with a factory custom package. Cat® engines, generators, enclosures, controls, radiators, transmissions — anything your project requires — can be custom designed and matched to create a one-of-a kind solution. Custom packages are globally supported and are covered by a one-year warranty after startup.

Full Range of Attachments

Large variety of factory-installed engine attachments reduces packaging time

Testing

Every engine is full-load tested to ensure proper engine performance

Product Support Offered Through Global Cat Dealer Network

- More than 2,200 dealer outlets
- Cat factory-trained dealer technicians service every aspect of your petroleum engine
- Cat parts and labor warranty
- Preventive maintenance agreements available for repair-before-failure options
- S•O•SSM program matches your oil and coolant samples against Caterpillar set standards to determine:
 - Internal engine component condition
 - Presence of unwanted fluids
 - Presence of combustion by-products
 - Site-specific oil change interval

Over 80 Years of Engine Manufacturing Experience

- Ownership of these manufacturing processes enables Caterpillar to produce high quality, dependable products.
 - Cast engine blocks, heads, cylinder liners, front and flywheel housings
 - Machine critical components
 - Assemble complete engine

Web Site

For all your petroleum power requirements, visit www.cat.com/oilandgas



3512E Non-Road PETROLEUM ENGINE

China Stage III 2237 bkW (3000 bhp)

STANDARD EQUIPMENT

Air Inlet System

Air-to-air aftercooled (ATAAC)
(512DW04, 512DW05, 512DW06, 512DW07)

Control System

ADEM A5 ECU, LH
With electronic fuel injector fuel system

Cooling System

ATAAC
Torque converter connections
Thermostats and housing, jacket water pump, gear-driven centrifugal (gear-driven centrifugal pumps)
Connections for radiator cooling
Dual outlets: 88.9 mm O.D. (3.5 in) elbow hose connections

Exhaust System

Land Well Service Engine:
Exhaust manifold, dry, slip joint with stainless steel wire seal
Four turbochargers with watercooled bearings (center-mounted)
Exhaust outlet, dual 203 mm (8 in) round flange
EQ SP, 250.95 mm bolt hole dia.

Flywheels & Flywheel Housing

Flywheel, SAE No. 0, 151 teeth
Flywheel housing, SAE No. 0

Fuel System

Primary fuel filter - 10 micron with water separation
Fuel priming pump
Fuel filter, RH spin-on type
Fuel transfer pump
Electronically controlled unit injectors

Instrumentation

No standard instrumentation
Service meter

Lube System

Crankcase breather — top-mounted
Oil cooler
Oil filler and dipstick — LH
Oil pump
Oil filter — LH spin-on type
Rear sump oil pan, 250-hour change interval
Oil pan drain valve, 3/4" NPT female connection
Fumes disposal
Scavenger pump

Mounting System

Trunion front support

Power Take-Offs

ATAAC
Front housing, two-sided

Protection System

ADEM A5 ECU system to provide customer programmable engine deration strategies to protect against adverse operating conditions
Emergency stop logic inputs provided at 70-pin customer interface connection

ATAAC

Single Air inlet shutoff

General

Paint, Cat yellow
Vibration damper and guard
Lifting eyes

OPTIONAL ATTACHMENTS

Air Compressors

Air Inlet System

Air cleaner - dual element with pre-cleaner
Remote air inlet adapters

Charging System

Charging alternators

Control System

Throttle position sensors

Cooling System

Coolant level sensor
Coolant conditioner
Connections - Hump Hose Type

Exhaust System

Flexible exhaust fitting
Elbows
Flange
Flange and exhaust adapters
Manifold

Fuel Systems

Flexible fuel lines
Fuel priming pumps, manual

Lube System

LH oil filters
Oil pan accessories
Oil pan front sump — 250 hrs
High capacity oil pan — 500 hrs

Power Take-Offs

Front Accessory Drives Auxiliary
Drive Shaft
Auxiliary Drive Pulleys
Front Stub Shaft
Front Crankshaft Adapter Pulleys

Starting System

Dual Hydraulic starters
Single Hydraulic Starter



3512E Non-Road China Stage III

PETROLEUM ENGINE


2237 bkW (3000 bhp)

PERFORMANCE CURVES

Turbocharged-Aftercooled

Well Service Rating

EM4074 — 2237 bkW (3000 bhp) @ 1900 rpm*



Heat Rejection Data								
Engine Speed	Engine Power		Rej to JW		Rej to Atmos		Rej to Exh	
rpm	bkW	bhp	bkW	Btu/min	bkW	Btu/min	bkW	Btu/min
1900	2237	3000	729	41445	158	8968	2188	124439

*Please contact dealer for performance data.




3512E Non-Road China Stage III


PETROLEUM ENGINE

2237 kW (3000 bhp)

PETROLEUM ENGINE



Right Side View



Front View

Engine Dimensions		
Length	2577.6mm	101.48 in
Width	1981.9 mm	78.03 in
Height	2206.1mm	86.85 in
Engine Weight (dry)	6400 kg	14,110 lb

Note: Do not use for installation design. See general dimension drawings for detail (Drawing #559-3883).

RATING DEFINITIONS AND CONDITIONS

IND-E Non-Road China Stage III

For service in China Well Service where maximum power is required for a short time for initial starting or sudden overload and 70% load limitations. For emergency service where standard power is unavailable (time at full load not to exceed 5% of the duty cycle).

Engine Performance is corrected to inlet air standard conditions of 99 kPa (29.31 in Hg) dry barometer and 25°C (77°F) temperature. These values correspond to the standard atmospheric pressure and temperature as shown in SAE J1995.

Performance measured using a standard fuel with fuel gravity of 35 degrees API having a lower heating value of 42 780 kJ/kg (18,390 BTU/lb) when used at 29°C (84.2°F) where the density is 838.9 g/L (7.001 lb/U.S. gal).

The corrected performance values shown for Cat engines will approximate the values obtained when the observed performance data is corrected to SAE J1995, ISO 3046-2, ISO 8665, ISO 2288, ISO 9249, ISO 1585, EEC 80/1269, and DIN 70020 standard reference conditions.

Information contained in this publication may be considered confidential. Discretion is recommended when distributing. Materials and specifications are subject to change without notice. The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.